

ISSUE DATE: SEPTEMBER 2019

CX3LG - STRATUS

MULTI-DECK SPECIFICATION SHEET



KYSOR WARREN
epta refrigeration

General Case Data	Case Length (ft)			
	4'	6'	8'	12'
Total Display Area (ft ²)	12.78	19.19	25.56	38.38
Cubic Capacity (ft ³)	21.42	32.16	42.85	64.33
Max Shelf Depth (in) [Top/Bottom]	14/20	14/20	14/20	14/20
Weight (lb)	-	-	-	-
Thermal Load (General)				
Discharge Air Velocity (fpm)	170-220	170-220	170-220	170-220
Fan Speed (rpm)	1200	1200	1200	1200
Discharge Air Temp (°F)	31	31	31	31
Conventional Thermal Load, Single (Btuh) one row of canopy LED	3860	5790	7720	11580
Parallel Thermal Load, Single (Btuh) one row of canopy LED	3713	5570	7426	11164
Additional Btuh per ft LED - Canopy / Shelf & Nose	13 / 11	13 / 11	13 / 11	13 / 11
Thermal Load (HFC)				
Evaporator Temperature (°F)	26	26	26	26
Superheat Setpoint (°F)	6 - 8	6 - 8	6 - 8	6 - 8
Estimated Refrigerant Charge (lbs)	1.241	1.846	2.579	3.925
Thermal Load (Glycol)				
Supply Temperature (°F)	20	20	20	20
Flow (GPM)	QTE	QTE	QTE	QTE
Fluid %	35	35	35	35
Pressure Drop (PSID)	QTE	QTE	QTE	QTE
Electrical Data (Amps/Watts)				
115V/60Hz, 1 Phase				
Fans	0.12	0.24	0.24	0.36
Canopy Lights (Per row)				
GE LED	0.22	0.33	0.44	0.67
Shelf Lights (Per row)				
GE LED	0.08	0.10	0.15	0.23

Defrost Data (off Cycle)			
Defrosts per Day	Failsafe Duration (min) ¹	Termination Temp (°F)	Drip Time (min)
6	25	47	2

¹ At ASHRAE conditions. For conditions above 75°F, 55% RH, increase defrost time by 15 min. Type I refrigerator, intended for use in an area where the environmental conditions are controlled and maintained that conditions do not exceed 75°F and 55% relative humidity. Kysor Warren, whose policy is one of continuous improvement, reserves the right to change at any time specifications, designs, or prices without incurring obligation. DOE 2017 Compliant

APPLICATIONS




The above case model has case lengths that are UL and NSF approved.

MULTI-DECK SPECIFICATION SHEET

Technical drawing of a window frame cross-section. The drawing includes the following dimensions and labels:

- Vertical Dimensions (Left):** 3, 36 $\frac{5}{8}$, 57.
- Horizontal Dimensions (Top):** 23, 6 $\frac{1}{8}$.
- Horizontal Dimensions (Bottom):** 3, 29, 29, 35, 42, 43 $\frac{1}{2}$, 8.
- Internal Dimensions:** 14, 18, 32, 16 $\frac{1}{4}$, 12, 6, 10 $\frac{1}{2}$, 14 $\frac{7}{8}$, 24 $\frac{1}{4}$.
- Labels:** "AIR SPACE" (vertical), "LOAD LIMIT LINE" (diagonal dashed line).
- Other Features:** A hatched area on the left indicates a specific material or insulation. A dashed line represents the load limit.

CX3LG PLAN VIEW (Single Coil)



KYSOR WARREN
epta refrigeration