

DX8UD - STRATUS
MULTI-DECK SPECIFICATION SHEET



Case Length (ft)			
General Case Data	4'	8'	12'
Total Display Area (ft ²)	22.60	45.20	67.85
Cubic Capacity (ft ³)	50.97	101.94	153.04
Max Shelf Depth (in) [Top/Bottom]	22/22	22/22	22/22
Weight (lb)	-	-	-
Refrigeration Data (General)			
Discharge Air Velocity (fpm)	185	185	185
Fan Speed (rpm)	1400	1400	1400
Discharge Air Temp (°F)	34	34	34
Conventional Thermal Load, Single (Btuh) unlighted	746	1489	2234
Parallel Thermal Load, Single (Btuh) unlighted	676	1349	2024
Refrigeration Data (HFC)			
Evaporator Temperature (°F)	28	28	28
Superheat Setpoint (°F)	6 - 8	6 - 8	6 - 8
Estimated Refrigerant Charge (lbs)	1.266	2.532	3.789
Refrigeration Data (Glycol)			
Supply Temperature (°F)	20	20	20
Flow (GPM)	QTE	QTE	QTE
Fluid %	35	35	35
Pressure Drop (PSID)	QTE	QTE	QTE
Electrical Data (Amps/Watts)			
115V/60Hz, 1 Phase			
Fans	0.17	0.33	0.60
Lights	0.12	0.24	0.36
Defrost Data (off Cycle)			
Defrosts per Day	Failsafe Duration (min) ¹	Termination Temp (°F)	Drip Time (min)
3	45	47	0

1 At ASHRAE conditions. For conditions above 75°F, 55% RH, increase defrost time by 15 min. Type I refrigerator, intended for use in an area where the environmental conditions are controlled and maintained that conditions do not exceed 75°F and 55% relative humidity. Heatcraft Worldwide Refrigeration, whose policy is one of continuous improvement, reserves the right to change at any time specifications, designs, or prices without incurring obligation. DOE 2017 Compliant

APPLICATIONS




The above case model has case lengths that are UL and NSF approved.

DX8UD - STRATUS


MULTI-DECK SPECIFICATION SHEET

DX8UD CROSS VIEW



Add 3" thickness for a pair of ends.

DX8UD PLAN VIEW



5201 Transport Blvd
Columbus, GA 31907
P: 800.866.5596 • F: 706.568.8990



www.kysorwarren.com

