ISSUE DATE: SEPTEMBER 2018

DX9LN - STRATUS





Case Length (ft)

	12'	
i	66.73	
3	164.98	W
2	22/22	
	-	



APPLICATIONS











General Case Data	4'	6'	8'	12'	
Total Display Area (ft²)		33.37	44.45	66.73	
Cubic Capacity (ft³)		82.49	110.03	164.98	
Max Shelf Depth (in) [Top/Bottom]	22/22	22/22	22/22	22/22	
Weight (lb)	-	-	-	-	
Refrigeration Data (General)					
Discharge Air Velocity (fpm)	200-300	200-300	200-300	200-300	
Fan Speed (rpm)		2200	2200	2200	
Discharge Air Temp (°F)		33	33	33	
Conventional Thermal Load, Single (Btuh) one row of canopy LED		8603	11461	17206	
Parallel Thermal Load, Single (Btuh) one row of canopy LED		7964	10609	15928	
Additional Btuh per ft LED - Canopy / Shelf & Nose	13 / 11	13 / 11	13 / 11	13 / 11	
Refrigeration Data (HFC)					
Evaporator Temperature (°F)	26	26	26	26	
Superheat Setpoint (°F)		6 - 8	6 - 8	6 - 8	
Estimated Refrigerant Charge (lbs)		3.795	5.077	7.589	
Refrigeration Data (Glycol)					
Supply Temperature (°F)	20	20	20	20	
Flow (GPM)		QTE	QTE	QTE	
Fluid %		35	35	35	
Pressure Drop (PSID)		QTE	QTE	QTE	
Electrical Data (Amps/Watts)					
115V/60Hz, 1 Phase					
Fans		0.83	0.83	1.65	
Canopy Lights (Per row)	<u> </u>				
GE LED	0.22	0.33	0.44	0.67	
Shelf Lights (Per row)					
GE LED	0.08	0.10	0.15	0.23	

Defrost Data (off Cycle)							
Defrosts per Day	Failsafe Duration (min) ¹	Termination Temp (°F)	Drip Time (min)				
6	18	47	0				


1 At ASHRAE conditions. For conditions above 75°F, 55% RH, increase defrost time by 15 min. Type I refrigerator, intended for use in an area where the environmental conditions are controlled and maintained that conditions do not exceed 75°F and 55% relative humidity. Kysor Warren, whose policy is one of continuous improvement, reserves the right to change at any time specifications, designs, or prices without incurring obligation. DOE 2017 Compliant





The above case model has case lengths that are UL and NSF approved.

DX9LN CROSS VIEW



Add 3" thickness for a pair of ends.

DX9LN PLAN VIEW

