## **MX1XP - STRATUS** SINGLE-DECK SPECIFICATION SHEET



		Case Length (ft)			
General Case Data		4'	6'	8'	12'
Total Display Area (ft <sup>2</sup> )	splay Area (ft <sup>2</sup> )		18.56	24.73	37.12
Cubic Capacity (ft <sup>3</sup> )		7.24	10.87	14.48	21.74
Max Shelf Depth (in) [Top/Bottom]		N/A	N/A	N/A	N/A
Weight (lb)		-	-	-	-
Thermal Load (General)					
Discharge Air Velocity (fpm)		250-300	250-300	250-300	250-300
Fan Speed (rpm)		1200	1200	1200	1200
Discharge Air Temp (°F)		26	26	26	26
Conventional Thermal Load, Single (Btuh) unlighted		1980	2970	3960	5940
Parallel Thermal Load, Single (Btuh) unlighted		1828	2742	3656	5484
Thermal Load (HFC)					
Evaporator Temperature (°F)		20	20	20	20
Superheat Setpoint (°F)		6 - 8	6 - 8	6 - 8	6 - 8
Estimated Refrigerant Charge (lbs)		0.990	1.473	2.059	3.134
Thermal Load (Glycol)					
Supply Temperature (°F)		20	20	20	20
Flow (GPM)		QTE	QTE	QTE	QTE
Fluid %		35	35	35	35
Pressure Drop (PSID)		QTE	QTE	QTE	QTE
Electrical Data (Amps/Watts)					
115V/60Hz, 1 Phase					
Fans		0.12	0.24	0.24	0.36
Defrost Data (off Cycle)					
Defrosts per Day Failsafe Duration (min) <sup>1</sup>		D: T (			
	Termination Temp (°F)	Drip Time (	min)		


1 At ASHRAE conditions. For conditions above 75°F, 55% RH, increase defrost time by 15 min. Type I refrigerator, intended for use in an area where the environmental conditions are controlled and maintained that conditions do not exceed 75°F and 55% relative humidity. Kysor Warren, whose policy is one of continuous improvement, reserves the right to change at any time specifications, designs, or prices without incurring obligation. DOE 2017 Compliant






The above case model has case lengths that are UL and NSF approved. MX1XP - STRATUS SINGLE-DECK SPECIFICATION SHEET

## **MX1XP CROSS VIEW**



Add 3" thickness for a pair of ends.

## MX1XP PLAN VIEW (Single Coil) (Single Coil)



5201 Transport Blvd Columbus, GA 31907 P: 800.866.5596 • F: 706.568.8990



fin D www.kysorwarren.com