QM3TE-12' w/Utilized End LEGACY **ISLAND SPECIFICATION SHEET**



Case Length (ft)

| 8' Side | |
|---------|--|



APPLICATIONS







| General Case Data | 4' Side | 8' Side | | |
|--|---------|-----------|--|--|
| Total Display Area (ft ²) | 16.84 | 22.92 | | |
| Cubic Capacity (ft ³) | | 42.88 | | |
| Max Shelf Depth (in) [Top/Bottom] | | 12" / 20" | | |
| Weight (lb) | | - | | |
| Refrigeration Data (General) | | | | |
| Discharge Air Velocity (fpm) | 250 | 250 | | |
| Fan Speed (rpm) | 1800 | 1800 | | |
| Discharge Air Temp (°F) | 29 | 29 | | |
| Conventional Thermal Load, Single (Btuh) one row of canopy LED | 5371 | 7348 | | |
| Parallel Thermal Load, Single (Btuh) one row of canopy LED | 4782 | 6542 | | |
| Additional Btuh per ft LED - Canopy / Shelf & Nose | 11 | 11 | | |
| Refrigeration Data (HFC) | | | | |
| Evaporator Temperature (°F) | 24 | 24 | | |
| Superheat Setpoint (°F) | | 6-8 | | |
| Estimated Refrigerant Charge (lbs) | | 15.82 | | |
| Refrigeration Data (Glycol) | | | | |
| Supply Temperature (°F) | | 20 | | |
| Flow (GPM) | | QTE | | |
| Fluid % | 35 | 35 | | |
| Pressure Drop (PSID) | QTE | QTE | | |
| Electrical Data (Amps/Watts) | | | | |
| 115V/60Hz, 1 Phase | | | | |
| ECM Fan Data (Amps/Qty) | 0.42/2 | 0.42/2 | | |
| Canopy Lights (Per row) | | | | |
| GE LED | 0.33 | 0.44 | | |
| Shelf Lights (Per row) | | | | |
| GE LED | 0.10 | 0.15 | | |
| | | | | |

| Defrost Data (off Cycle) | | | | | |
|--------------------------|--------------------------------------|-----------------------|-----------------|--|--|
| Defrosts per Day | Failsafe Duration (min) ¹ | Termination Temp (°F) | Drip Time (min) | | |
| 4 | 40 | 47 | 0 | | |

1 At ASHRAE conditions. For conditions above 75°F, 55% RH, increase defrost time by 15 min. Type I refrigerator, intended for use in an area where the environmental conditions are controlled and maintained that conditions do not exceed 75°F and 55% relative humidity. Heatcraft Worldwide Refrigeration, whose policy is one of continuous improvement, reserves the right to change at any time specifications, designs, or prices without incurring obligation. DOE 2017 Compliant








The above case model has case lengths that are UL and NSF

QM3TE-12 CROSS VIEW


34.05 34.05 31.70 31.70 7.79 7.794

QM3TE-4 END CASE CROSS VIEW



Add 3" thickness for a pair of ends.

QM3TE-12 PLAN VIEW



5201 Transport Blvd Columbus, GA 31907

P: 800.866.5596 • F: 706.568.8990



