



LOW TEMPERATURE REACH-IN SELF CONTAINED MERCHANDISER

TECHNICAL INFORMATION

GENERAL CASE DATA	2 Doors	3 Doors	4 Doors
Exterior Dimensions (L x H x D) (in)*	57.7 x 80.9 x 31.8	84.1 x 80.9 x 31.8	110.5 x 80.9 x 31.8
Interior Dimensions (L x H x D) (in)*	54.0 x 64.2 x 25.6	80.0 x 64.2 x 25.6	106.0 x 64.2 x 25.6
Total Display Area TDA (ft ²)	20.8	31.2	41.5
Storage capacity (ft ³)	31.8	47.7	63.6
Standard # of Rows & Depth of Shelving**	5 Rows @ 20" Depth	5 Rows @ 20" Depth	5 Rows @ 20" Depth
Product Temperature Range (°F)	(-15) - 0	(-15) - 0	(-15) - 0
*2.44" thickness for each end included in the dimensions above			
**Shelves can be positioned at 2 different angles and varying heights			

PACKAGING (General)			
Packaging Dimensions (L x H x D) (in)	62.9 x 88.6 x 36.2	89.4 x 88.6 x 36.2	122.0 x 88.6 x 36.2
Net Weight (lb)	593	809	1186
Gross Weight (lb)	701	981	1402

THERMAL LOAD (GENERAL)			
Refrigerant Type	R-290	R-290	R-290
Estimated Refrigerant Charge Per Circuit (grams/oz)	150/5.29	150/5.29	150/5.29
Compressor HP	1 1/4	5/8 (x2)	1 1/4 (x2)
Refrigerant Circuits	1	2	2
Energy Consumption (kWh/day)	12.7	19.8	27.1
Rejected Heat (BTU/h)	3341.8	4944.5	6581.3

ELECTRICAL DATA (AMPS/WATTS)			
Power Supply (Volts/Hertz/Phase)	115 V / 60 HZ / 1 ph	115 V / 60 HZ / 1 ph	115 V / 60 HZ / 1 ph
Minimum Circuit Ampacity (A)	14.14	14.66	25.77
Maximum Overcurrent Protection (A)	20	20	30
Rated Amps (A)	13	16	24
Plug Type	NEMA L5-20P	NEMA L5-20P	NEMA L5-30P

DEFROST DATA	Hot gas
Defrost per Day	4
Termination Temp (°F)	2

Type I refrigerator, intended for use in an area where the environmental conditions are controlled and maintained that conditions do not exceed 75°F and 55% RH.

Kysor Warren Epta US, whose policy is one of continuous improvement, reserves the right to change at any time specifications, designs, or prices without incurring obligation.

VALZER KW



KYSOR WARREN
epta refrigeration

LOW TEMPERATURE REACH-IN SELF CONTAINED MERCHANDISER

