

VALZER KW



KYSOR WARREN
epta refrigeration

LOW TEMPERATURE REACH-IN SELF CONTAINED MERCHANDISER



Frozen food



Ice cream



TECHNICAL FEATURES



Incorporated
condensing
unit



Hot gas
defrost



Ventilated



LED lighting



High
Efficiency
fans



Propane
Refrigerant
Gas (R290)



Plug type 2-3D:
NEMA L5-20P
9.8 ft. cord length



Plug type 4D:
NEMA L5-30P
9.8 ft. cord length



*LOW TEMPERATURE REACH-IN
SELF CONTAINED MERCHANDISER*

TECHNICAL INFORMATION

GENERAL CASE DATA	2 Doors	3 Doors	4 Doors
Exterior Dimensions (L x H x D) (in)*	57.63 x 81.20 x 32.10	84.03 x 81.20 x 32.10	110.42 x 81.20 x 32.10
Interior Dimensions (L x H x D) (in)*	52.75 x 64.28 x 25.18	79.15 x 64.28 x 25.18	105.54 x 64.28 x 25.18
Total Display Area TDA (ft ²)	20.8	31.2	41.5
Storage capacity (ft ³)	31.8	47.7	63.6
Standard # of Rows & Depth of Shelving**	5 Rows @ 20" Depth	5 Rows @ 20" Depth	5 Rows @ 20" Depth
Product Temperature Range (°F)	(-15) - 0	(-15) - 0	(-15) - 0
*2.44" thickness for each end included in the dimensions above			
**Shelves can be positioned at 2 different angles and varying heights			

PACKAGING (General)			
Packaging Dimensions (L x H x D) (in)	62.9 x 88.6 x 36.2	89.4 x 88.6 x 36.2	122.0 x 88.6 x 36.2
Net Weight (lb)	593	809	1186
Gross Weight (lb)	701	981	1402

THERMAL LOAD (GENERAL)			
Refrigerant Type	R-290	R-290	R-290
Estimated Refrigerant Charge Per Circuit (grams/oz)	150/5.29	150/5.29	150/5.29
Compressor HP	1 1/4	5/8 (x2)	1 1/4 (x2)
Refrigerant Circuits	1	2	2
Energy Consumption (kWh/day)	12.7	19.8	27.1
Rejected Heat (BTU/HR)	2660	4570	5250

ELECTRICAL DATA (AMPS/WATTS)			
Power Supply (Volts/Hertz/Phase)	115 V / 60 HZ / 1 ph	115 V / 60 HZ / 1 ph	115 V / 60 HZ / 1 ph
Minimum Circuit Ampacity (A)	14.14	14.66	25.77
Maximum Overcurrent Protection (A)	20	20	30
Rated Amps (A)	13	16	24
Plug Type	NEMA L5-20P	NEMA L5-20P	NEMA L5-30P

DEFROST DATA	Hot gas
Defrost per Day	4
Termination Temp (°F)	2

Type I refrigerator, intended for use in an area where the environmental conditions are controlled and maintained that conditions do not exceed 75°F and 55%RH.

Kysor Warren Epta US, whose policy is one of continuous improvement, reserves the right to change at any time specifications, designs, or prices without incurring obligation.

LOW TEMPERATURE REACH-IN SELF CONTAINED MERCHANDISER

